

Amendments to the Claims:

This listing of claims will replace all prior listings of claims in the application.

Listing Of Claims:

Claim 1 (canceled).

Claim 2 (canceled).

Claim 3 (previously presented): A remote control system comprising:

a remote control apparatus; and

a first apparatus controlled by said remote control apparatus;

wherein said remote control apparatus comprises: at least one key switch for remote control; and a first transmitting device that repeatedly transmits a control signal corresponding to said key switch while said key switch is being operated and that inhibits the transmission of the control signal in accordance with reception of a predetermined signal from said first apparatus;

wherein said first apparatus comprises: a first determination device that determines whether the control signal, transmitted by said first transmitting device, is suitable for repeated control; and a second transmitting device that transmits an inhibition instruction signal for inhibiting said first transmitting device from repeatedly transmitting the control signal in accordance with a determination by said first determination device.

Claim 4 (original): A remote control system according to claim 3, wherein said first apparatus comprises:

a second determination device that determines whether the control signal transmitted by said first transmitting device has been normally received; and

wherein said second transmitting device transmits the inhibition instruction signal and an acknowledgement signal indicative of normal reception of the control signal when said second determination device determines that the control signal has been normally received, and said first determination device determines that the control signal is unsuitable for repeated control.

Claim 5 (previously presented): A remote control system comprising:

a remote control apparatus; and

a first apparatus controlled by said remote control apparatus;
wherein said remote control apparatus comprises: at least one key switch for remote control; and a first transmitting device that repeatedly transmits a control signal corresponding to said key switch while said key switch is being operated and that inhibits the transmission of the control signal in accordance with reception of a predetermined signal from said first apparatus;
wherein said remote control apparatus comprises: a first determination device that determines whether the control signal corresponding to said key switch, transmitted by said first transmitting device, is suitable for repeated control; and a second determination device that determines whether a response to the control signal has been received from said first apparatus;
and
wherein said first transmission device is operable to inhibit repeated transmission of the control signal when said first determination device determines that the control signal is unsuitable for repeated control, and said second determination device determines that the response has been received.

Claim 6 (canceled).

Claim 7 (previously presented): An electronic apparatus that is remotely controlled by a remote control apparatus, comprising:

a first determination device that determines whether a control signal transmitted by the remote control apparatus is suitable for repeated control; and

a transmitting device that transmits an inhibition instruction signal for inhibiting repeatedly transmission of the control signal in accordance with a determination by said first determination device.

Claim 8 (original): An electronic apparatus according to claim 7, further comprising a second determination device that determines whether the control signal has been normally received; and

wherein said transmitting device transmits the inhibition instruction signal and an acknowledgement signal indicative of normal reception of the control signal when said second

determination device determines that the control signal has been normally received, and said first determination device determines that the control signal is unsuitable for repeated control.

Claim 9 (canceled).

Claim 10 (original): A remote control method of remotely controlled by a remote control apparatus, comprising:

a first determination step of determining whether a same control signal repeatedly transmitted by the remote control apparatus is suitable for repeated control; and

a transmitting step of transmitting an inhibition instruction signal for inhibiting the repeatedly transmission of the control signal in accordance with a determination in said first determination step.

Claim 11 (canceled).

Claim 12 (previously presented): A program for causing a computer to execute a remote control method of remotely controlled by a remote control apparatus, comprising:

a first determination module for determining whether a control signal transmitted by the remote control apparatus is suitable for repeated control; and

a transmitting module for transmitting an inhibition instruction signal for inhibiting repeated transmission of the control signal in accordance with a determination in said first determination module.

Claim 13 (original): A remote control system comprising:

a remote control apparatus; and

a first apparatus controlled by said remote control apparatus;

wherein said first apparatus comprises: a first determination device that determines whether a control signal has been normally received from said remote control apparatus; and a returning device that returns an acknowledgement signal indicative of normal reception of the control signal when said determination device determines that the control signal has been normally received; and

wherein said remote control apparatus comprises: at least one key switch for remote control; a transmitting device that repeatedly transmits a control signal corresponding to said key switch while said key switch is being operated; a second determination device that determines whether the control signal corresponding to said key switch is suitable for repeated control when the acknowledgement signal is returned from the apparatus to be controlled; and an inhibition device that inhibits said transmitting device from repeatedly transmitting the control signal when said second determination device determines that the control signal corresponding to said key switch is unsuitable for repeated control.

Claim 14 (original): A remote control apparatus that remotely controls a first apparatus; comprising:

at least one key switch for remote control;

a transmitting device that repeatedly transmits a control signal corresponding to said key switch while said key switch is being operated;

a determination device that determines whether the control signal is suitable for repeated control when an acknowledgement signal indicative of normal reception of the control signal is returned from the apparatus to be controlled in response to the control signal; and

an inhibition device that inhibits said transmitting device from repeatedly transmitting the control signal when said determination device determines that the control signal is unsuitable for repeated control.

Claim 15 (original): A remote control method of remotely controlling a first apparatus by a remote control apparatus, comprising:

a transmitting step of repeatedly transmitting a control signal corresponding to a key switch for remote control while the key switch is being operated;

a determination step of determining whether the control signal is suitable for repeated control when an acknowledgement signal indicative of normal reception of the control signal is returned from the apparatus to be controlled in response to the control signal; and

an inhibiting step of inhibiting repeated transmission of the control signal when it is determined in said determination step that the control signal is unsuitable for repeated control.

Claim 16 (original): A program for causing a computer to execute a remote control method of remotely controlling a first apparatus by a remote control apparatus, comprising:

- a transmitting module for repeatedly transmitting a control signal corresponding to a key switch for remote control while the key switch is being operated;
- a determination module for determining whether the control signal is suitable for repeated control when an acknowledgement signal indicative of normal reception of the control signal is returned from the apparatus to be controlled in response to the control signal; and
- an inhibiting module for inhibiting repeated transmission of the control signal when it is determined by said determination module that the control signal is unsuitable for repeated control.

Claims 17-26 (canceled).